



Models: Ultra 250, 600 and 1300



Ultra 1300 Model

Ultra 250/600 Models



Ultra 600 with heat deflector and external chemical injection system.



Water Broom shown with back view of the Ultra 1300 model.

Propane-Fired Steam Cleaning Equipment

Therma-Kleen's series of propane-fired, steam cleaners, Models Ultra 250, 600 and 1300 are clean burning, compact systems, designed to clean, de-grease and sanitize with high pressure and low water flow. Combined with steam temperatures, they will provide an environmentally positive workplace by generally eliminating the need for most chemicals, so as to be able to offer an efficient and time saving solution to maintenance and sanitation requirements. Our Model Ultra 1300 is our most powerful model, designed to clean and sanitize large areas and equipment when time is a factor. All of our models require only a vaporous 30 or 40 lb. LPG Cylinder, 110V, a standard 15a electrical outlet, an electric extension cord and a water hose to your water outlet. Our Ultra 250 models can be purchased with several low water volume pumps designed to meet your specific cleaning needs. All our models are equipped with standard blue-colored, powder coated, painted bodies. Stainless steel bodies are available by request.

Propane Fired Steam Cleaners

MODELS:	ULTRA 1300	ULTRA 600	ULTRA 250
Water Pressure	1300 psi / 85 bar	600 psi / 41 bar	250 psi / 17 bar
Max. Water Temp.	350 F / 176 C	350 F / 176 C	350 F / 176 C
Water Volume	2.2 gpm	1.5 gpm	1.5 gpm
Dimensions	24" w, x 28" l, x 36"h	18" w, x 23"l, x 32"h	18"w, 23"l, 32"h.
Weight-Std.-Painted:	195 lb.	100 lb.	95 lb.
Stainless steel	190 lb.	95 lb.	90 lb.
Fuel:	Vaporous L.P. Gas on all models. Option: Natural Gas		
BTU/hr.	200,000	130,000	130,000
Electrical:	13a/115/60hz	6.8a/115v/60hz	6.8a/115v/60hz.
	Option: 220v/ 60 or 50 hz		

Safety Features on all propane models:

Electronic Pilot Ignition, Hi-Temperature Limit Switch, Unloader and flow switch.

Accessories:

25 ft. steam hose for the Ultra 250 and Ultra 600 models; 50 ft. steam hose for the Ultra 1300; fan and blast nozzles, LPG regulator, 4 ft. wand with trigger gun, strap and manual.

Pump Maintenance:

The Ultra 250 pump requires no maintenance.

The Ultra 600 and Ultra 1300 pumps are factory sealed and do not require any maintenance. The Ultra 1300 model also has an internal chemical injection system.



Clean, de-grease, sanitize and remove gum with the combination of steam temperature and pressure.

All Electric 220 volt/ 3 phase Steam Cleaners

MODELS:	ULTRA 250E	ULTRA 600E
---------	------------	------------



Ultra 250E / 600E

Water Pressure:	250 psi / 17 bar	600 psi / 41 bar.
Max. Water Temp.:	100-130F water temperature rise	
Water Volume:	1.5 g.p.m.(smaller volumes available)	
Dimensions:	35" l, x 22"H, x 10" w	
Weight:	145 lb.	
Electrical current:	220 volt, 3 phase (440 available)	
Amperage Draw:	52 amps	
Body style:		

Available in powder coated paint or stainless steel. Push handle is 38" from the floor; 2 swivel and 2 rigid casters.

Accessories:

Fan and blast nozzle, 25 ft. steam hose, 4 ft. wand with trigger gun, power cord and steam hose holder.

Accessories



2.5 ft. and snub nose wands



Heat Deflector



External soap injection system



Sewer Cleaning nozzle



Stack cleaner



Surface cleaner



In-line water softening system

Also:

25, 50, & 100 ft. Steam hoses

30 lb. and 40 lb. Vaporous L.P. Tanks

Water broom (Shown on the front side)